

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings of claims in the application:

Listing of Claims:

Please cancel claims 1, 2, 4, 5 and 10, without prejudice, so that the pending claims read as follows:

1-2 . (canceled)

3. (previously presented) A method for establishing a connection between a receiver terminal and a transmitter terminal, located at a distance from each other, comprising the steps of:

sending from said transmitter terminal toward said receiver terminal both a first tightly bundled lightwave carrying data signals and a second wider angle beacon lightwave to assist in receptive alignment of said first data signal lightwave;

using an acquisition sensor and a receiving sensor at said receiver terminal to acquire said wider beacon lightwave and generate internal control signals to better align said receiving sensor to receive said data signals;

using said receiving sensor to receive said data signals once proper alignment has been achieved;

wherein light from said receiving sensor is conducted over a first lightwave fiber to a diplexer, and light is split off from this diplexer and conducted to a detector over a second lightwave fiber, which provides an additional signal for making acquisition easier;

further wherein light, which arrives via the first lightwave fiber and the diplexer, is also conducted to an optical waveguide coupler, in which this light, and light from a local laser conducted through a third lightwave fiber, are mixed, wherein the mixed light is split into two

parts, each of which reaches a further detector via respective further lightwave fiber for generating at least one error signal.

4-5. (canceled)

6. (presently presented) A device for receiving a first tightly bundled lightwave carrying data signals and a second wider angle beacon lightwave from a distant transmitter, comprising:

a receiver telescope and a fine alignment mechanism with a beam splitter to receive both said first and second lightwaves, which beam splitter is designed to provide light via optical fibers to an acquisition sensor, as well as to a receiving sensor in order to properly orient said device for data reception,

wherein, when properly oriented, said receiving sensor receives said data signals from said first lightwave;

wherein the receiving sensor is connected via a first lightwave fiber with a diplexer, downstream of which a detector is connected via a second lightwave fiber and provides an additional signal for making acquisition easier;

further comprising an optical waveguide coupler, whose input is connected via a third lightwave fiber with the diplexer and which, with coherent heterodyne reception, mixes light arriving from the diplexer and light from a local laser, conducted over a fourth lightwave fiber, and split into two parts, which reach a detector via a respective further lightwave fiber for generating at least one error signal.

7. (previously presented) The device in accordance with claim 6, further comprising a first detector connected with a discriminator, which delivers an additional signal to a system control.

8. (original) The device in accordance with claim 7, further comprising a second discriminator, connected downstream of said detector, which delivers at least one error signal to said system control.

9. (previously presented) The device in accordance with claim 7, wherein the receiving sensor is connected to a control, which provides command signals for a discriminator.

10. (canceled)